

SRA-900

SEA RIB™ ALUMINIUM

SEARIB

TWIN OUTBOARD - "D-SHAPE" COLLAR



STRENGTH & MODULAR

Zodiac Milpro™ Sea Rib™ Aluminium are built for demanding professional and military users and designed to be strong and reliable.

SRA-900 boat features "D-shape" collar technology, increasing the useable deck area. It can be fitted as well with a standard round collar. The collar is readily removable to provide easy maintenance.

The SRA-900 aluminium deck integrates deck tracks, allowing rapid re-configuration to suit the mission.

It is fully versatile and capable multi-role boat making it operational in all sea conditions.



CAPACITY

. Max. number of pax (ISO6185) :	Cat. C :	16	16
	Cat. B :	8	8
. Maximum payload (certificate) :	Cat. C :	2958 kg	6521 lb
	Cat. B :	2333 kg	5143 lb
. Maximum payload (ID plate) :	Cat. C :	2710 kg	5975 lb
	Cat. B :	2090 kg	4608 lb
. Floorboard net area :		15,26 m ²	164,26 ft ²
. Floorboard usable area :		12,90 m ²	138,85 ft ²
. Buoyancy tube volume :		2,48 m ³	87,72 ft ³

DIMENSIONS

. Overall length :	8,32 m	27' 4"
. Inside length :	5,43 m	17' 10"
. Overall width :	3,02 m	9' 11"
. Inside width :	2,40 m	7' 10"
. Overall height :	1,79 m	5' 10"
. Draft / Draught :	0,60 m	1' 12"
. Weight empty :	1430 kg	3153 lb
. Boat weight in max.payload condition :	5240 kg	11552 lb
. Buoyancy tube diameter :	0,62 m	24"

ENGINE

. Propulsion system :	Outboard, Single	
. Shaft length :	Twin : XXL - 30"	XXL - 30"
. Recommended power :	Twin : 2 x 300 HP	2 x 224 kW
. Maximum power :	Twin : 2 x 350 HP	2 x 261 kW
. Maximum weight :	Twin : 2 x 370 kg	2 x 816 lb

SAFETY / INFLATION

. Design category (2013/53/EU) :	B - C	
. Airtight compartments on main tube :	5	
. Tube air pressure :	240 mbar	3,4 PSI



FABRIC

CSM / Neoprene Duratane™ fabric

. Buoyancy tube :	1670 dtx, polyester
. Baffle :	black, 1100 dtx, polyester

ZODIAC MILPRO INTERNATIONAL

11 rue de Reuilly
75012 Paris - France

www.zodiacmilpro.com

Fax: +33 1 73 01 77 56
info.milpro@zodiacmilpro.com

www.milpro.com

SASU with a registered capital of 2 500 000 € - RCS 534 317 011

HULL CONSTRUCTION

. Hull material :	Marine grade aluminium alloy
. Airtight compartment :	3
. Deck :	Self-bailing
. Deck modularity :	Tracks for modular deck configuration
. Underdeck :	Fuel tank cavity
. Underdeck access :	Deck maintenance panel and hatch
. Integrated bow box / anchor locker	1
. Aft storage locker in transom well	1
. Hull drain :	1

TUBE CONSTRUCTION

. Fabric :	Duratane®, 1670 dtx, polyester, CSM / Neoprene
. Color :	Grey, black, orange
. Tube/hull attachment :	Removable slide-on tube with bolt rope
. Intercommunication inflation valve on tube :	6
. Peripheral rubbing strake, flat profile, black :	3
. Additional bow rubbing strake, black :	2

STERN TRANSOM

. Large flow self-bailer :	2
. Electric bilge pump, ignition protected :	1
. Manual bilge pump :	1

OPTIONAL EQUIPMENT

TUBE EQUIPMENT

. Durarib™ tube
. Diver door
. Bow protection net / Anchor guide / Treadmaster :
. Lettering / Logo :

STRUCTURAL EQUIPMENT

. Stand-up console (aluminium - large - 2 pax)
. T-top / Lateral covers
. Jockey seat with storage (1 or 2 pax.)
. Jockey seat with fuel tank (1 or 2 pax.)
. Jockey seat frame only (2 or 3 pax.)
. Bolster large (2 pax)
. Bolster large with storage (2 pax)
. Shock mitigation seat (single / duo)
. Foot strap
. Roll-bar / mast
. Self righting system
. Rope-guard
. Rope reel
. Bow post / Tow post
. Gun-mount
. Dive cylinder support (4 / 6)
. Overall cover (boat only / boat & engine)

TOWING / LIFTING

. Bow mooring point - integrated eye :	1
. Transom towing point - integrated eye :	1+1
. Bow lifting point - integrated eye :	1+1
. Transom lifting point - integrated eye :	1+1
. Bow post :	1
. Tow post :	1

HANDLING / LIFELINE

. Exterior lifeline on D-rings :	1+1
----------------------------------	-----

FUEL SYSTEM

. Built-in fuel tank :	2 x 310 L	2 x 82 gal US
. Fuel tank material :	Rotomolded polyethylene	
. Fuel sensor :	2	
. Fuel fill on bow box :	2	
. Fuel vent :	2	
. Fuel shut off valve, 2 ways :	2+2	

OTHER EQUIPMENT

. Bellows foot pump + hose :	2
. Repair kit (manometer included) :	1
. Paddle (telescopic) :	2

NAVIGATION COMMUNICATION

. VHF / AIS / Intercom / GPS / Radar / Sounder
. Navigation lights / Deck lights / Strobe light / Search light
. Hailer / Siren / Radar reflector / EPIRB / SART

ACCESSORIES

. Trailer
. V towing bridle bow / aft
. Lifting sling
. Mooring kit : anchor, chain, rope
. Watertight bow bag / pouch / collar bag
. Ancillary equipment : hook, life jacket, extincor, mirror, life ring...
. Ladder (flexible / rigid)

PROPULSION SYSTEM

. Triple engine configuration
. Engine (any brand or power) / rigging kit
. Waterproof indirect / Underwater direct bag OB engine
. Complete electric system with battery(ies)
. Complete fuel system with separator filter(s)
. Hydraulic or mechanical steering system

MISCELLANEOUS

. Training (commissioning, maintenance, piloting, airdrop...)
